

# SOLAR SPARROW



Ultraviolet



Riviera Blue



Ivy



Americano



Canyon Flame


 Up To 40 Miles

 Integrated Wiring

 Gates Belt Drive



Performance: **4 riding modes, 500W & Cadence/Torque sensor**



Comfort & Safety: **Adjustable stem, ergo grips, and front/rear lights**



Rear Rack & Fenders: **Stay clean with 50lbs capacity**



Front & Seat Post Suspension: **Uni-Fork & SR Suntour NCX seatpost**



Drivetrain: **Gates Carbon Belt Drive**



Hydraulic Disc Brakes: **Stop confidently with Tektro E350**

# SOLAR SPARROW SPECIFICATIONS

GENERAL INFORMATION		FRAME	
Range	Up to 40 miles	Frame Material	Aluminum 6061 Alloy
Speed	28 mph max	Frame Style	Step Through
Weight	53 lbs	Rear Rack	Aluminum (50 lbs max)
Weight Capacity	300 lbs	DRIVETRAIN	
Sensor System	Torque & Cadence	Brakes	Tektro E350 Hydraulic
Safety Certifications	SGS Certified, UL 2849	Brake Levers	Adjustable w/ motor cut-off
SIZING		Brake Rotor	180mm front & rear
Rider Heights	4'11" - 5'10"	Derailleur	Single Speed
Seat Tube Length	13 inches	Freewheel	Gates Flywheel, 20T
Total Length	71 inches	Chain	Gates Belt Drive
Wheelbase	44 inches	Crank Set	Aluminum alloy, 170mm
Standover Heights	16 inches	Chainring	Gates Chainring, 60T
Reach	16 inches	Pedals	Polypropylene
Saddle Heights	34 - 40 inches	ELECTRONIC	
Stem	90mm Adjustable	Motor	500W Bafang Hub
SUSPENSION & WHEELSET			
Front Fork	Uni-Fork Suspension, 30mm Travel	Battery	48V, 10.5Ah, 504Wh
Seatpost	SR Suntour NCX Suspension	Controller	Custom 48V, 20 Amp in-frame
Saddle	Velo Wide Comfort	Display	Left side color LCD
Tires	Kenda Kwik Six 26' x 2.4"	Headlight	200 lux dual beam LED
Rim	Double-walled aluminum	Rear Light	Standard & flash
Spokes	12G Front, 12G Rear	Charger	48V, 2 Amp
Front Hub	Thru-Axle	Throttle	Thumb throttle, left
		USB Port	Type C USB charging